

## 700

Interior & Exterior High Quality Acrylic Emulsion Paint

### DESCRIPTION:

- **Blato 700** is a high quality emulsion paint have been developed and formulated to provide high hiding power ,lasting whiteness and great coverage for interior & exterior application.
- It provides a smooth sheen finish to interior walls.
- It have low VOC, hence maintaining a healthy home

### USES:

- **Blato 700** is used on interior & exterior walls, ceilings and hard & soft boards.

### FEATURES AND BENEFITS:

- Smooth Sheen Finish.
- High hiding power and coverage
- Low VOC
- Cost of paint is low
- Good adhesion
- Provides uniform finish

### SURFACE PREPARATION:

- **New surfaces :**

- New concrete must age at least 28 days, its pH must be less than 10 and it must be completely dry prior to priming
- Ensure that all dust, dirt and foreign matter are scraped and brushed away. Also ensure the surfaces are free from salts, oil, grease and ridges.
- **PRIMER:** Apply a coat of diluted **Blato Sealer Coat 101** and allow drying for 6-8 hours.
- **PUTTY:** Smoothen the surface by filling dents with a thin coat of **Blato finish** putty and allow drying for 4-6 hours. Sand the surface with emery paper no.180 and wipe clean.
- **PRIMER:** Apply another coat of **Blato Sealer Coat 101** and allow drying for 6-8 hours. Before application of topcoat, sand the surface with emery paper no.320 and wipe clean.
- **Old surface:**
  - Sand all glossy, rough, and patched surfaces. Feather back all rough edges to sound surface by sanding.
  - **PUTTY:** repair the surface by filling dents cracks with a thin coat of **Blato finish** wall putty and allow drying for 4-6 hours. Sand

the surface with emery paper no.180 and wipe clean.

- **PRIMER:** Apply one coat of diluted **Blato Sealer Coat 101** and allow drying for 6-8 hours. Before application of topcoat, sand the surface with emery paper no.320 and wipe clean.

### APPLICATION:

**Stir thoroughly before using and occasionally when in use.**

- Dilute the paint with 30-40% water by volume.
- Apply two coats
- **Blato 700** is applied by using brush or roller.

### coverage

- 1 kg cover 4-6 m<sup>2</sup> one coat

### STANDARD:

- **SASO 470 : 2016**

### TECHNICAL DATA

Color	White
Density @ 25 °c	1.6±0.02 gm/cm <sup>3</sup>
PH @ 25 °c	8.5-9
Finish	Flat finish ( gloss <10 @85°
Solvent	Potable water
Dry Time: To Touch	60minutes
To Recoat	3-4 hours

### CLEAN UP INSTRUCTIONS:

- Clean up solvent: Clean, potable water

### PRECAUTIONS:

- Avoid painting when the temperature is below 10 degrees Celsius. Painting is not recommended if the moisture content and alkalinity of the walls is high. Moisture content of the walls should be below 16% and alkalinity of the wall should be below pH-10.

### PACKAGING:

- 20 Kg Pails.
- 25 kg pails
- 5kg cans

### SHELF LIFE / STORAGE:

- Storage: must be stored in a cool, dry elevated place and protected from high humidity.
- Shelf Life: Up to 12 months in unopened containers, if stored as specified above.

### ENVIRONMENTAL & SAFETY

#### PRECAUTIONS:

- Do not store near food, drink or animal feed.
- Keep out of reach of children.
- Do not dispose of unwanted paint into drains, water sources or open sewers.
- For a full MSDS on this product, contact to BLATO .