

LUSTER-2000 High Quality Gloss Enamel Paint

DESCRIPTION:

- LUSTER-2000 is a superior quality synthetic coating based on a high performance Alkyd Resin with outstanding alkali resistance and superlative binding properties.
- It is designed to give the advantage of opacity, durability and hiding power.

USES:

- Recommended for Interior use on all new or old surfaces such as bricks, concrete surfaces, cement, gypsum boards, artificial stone and new iron (after priming).

FEATURES AND BENEFITS:

- Gloss finishes
- Excellent durability
- High hiding power
- Excellent leveling
- Brilliant white
- Lead free & yellowing resistance
- Washable

SURFACE PREPARATION:

1. Cementitious Surface :

- Ensure that all dust, dirt and foreign matter are scraped and brushed away. Also ensure the surfaces are free from salts, oil, grease and ridges.
- **PRIMER:** Apply a coat of diluted **Sealer-50** allow drying for 6-8 hours.
- **PUTTY:** Smoothen the surface by applying two coat of MBC Cement putty and allow drying for 4-6 hours. Sand the surface with emery paper no.180 and wipe clean.

- **Apply third coat from MBC-Oil putty** then allow drying for 6-8 hours. Sand the surface with emery paper no.320 and wipe clean.

2. Metal Surface:

- Make sure the surface is clean, clear, sound and free of grease , rust and dust.
- Apply one coat of **MBC-Anti rust primer** by brush, roller or spray onto metal surfaces.

3. Wood Surface :

- Make sure the surface is clean, clear, sound and free of grease , rust and dust.
- Apply two coats from **MBC-Oil putty** then allow drying for 6-8 hours. Sand the surface with emery paper no.320 and wipe clean.

APPLICATION:

- Stir thoroughly before using and occasionally when in use.
- Dilute the paint using white spirit solvent.
- Apply two coats of diluted Luster666
- Allow 15-18 hours between each coat for complete drying.
- Luster666 is applied by using brush ,roller or spray gun .

COVERAGE:

12 - 15 m²/Ltr/Coat (depending on surface condition)

TECHNICAL DATA

Color	White & tinted by tinting machine
Density @ 25 °c	1.15 ±0.02 gm/cm ³
Thinner type & Dilution %	(white spirit) 10 % with Brush and Roller use 15 % with air spraying
Finish	gloss
Flash Point	40°C
Initial drying time	3 hours
Recoat Time	15-18 hours
Final drying time	24hours

CLEAN UP INSTRUCTIONS:

- Clean up solvent: Clean, white spirit

PACKAGING:

- 4 USG Pails
- 3 LITTER

SHELF LIFE / STORAGE:

- Storage: must be stored in a cool, dry elevated place and protected from high humidity.
- Shelf Life: Up to 12 months in unopened containers, if stored as specified above.

ENVIRONMENTAL & SAFETY

PRECAUTIONS:

- Do not store near food, drink or animal feed.
- Keep out of reach of children.
- Do not dispose of unwanted paint into drains, water sources or open sewers.
- For a full MSDS on this product, contact to MBC