

## ANTI-RUST PRIMER

### DESCRIPTION:

- MBC ANTI-RUST PRIMER is a high-solids rust-inhibitive alkyd primer with anti-corrosive properties. It is easy to apply by spray, is fast drying, and can be top-coated with alkyd paints.

### USES:

- MBC ANTI-RUST PRIMER is ideal for architectural and light commercial construction, and is ideal for application on steel to protect against atmospheric exposure. With excellent impact resistance, it is also suitable for use on vehicles.

### FEATURES AND BENEFITS:

- Easy to use.
- Fast drying.
- Easy to smooth down (sand).
- Impact resistant.

### SURFACE PREPARATION:

- Ensure that all dust, dirt and foreign matter are scraped and brushed away. Also ensure the surfaces are free from salts, oil, grease and ridges.

### APPLICATION:

- Add 5-10% of white spirit for dilution
- Apply one coat of diluted MBC ANTI-RUST PRIMER by brush, roller or spray.
- Sand lightly and apply another coat if needed.
- Apply the top coat LUSTER enamel paint
- Clean tools using white spirit.

### COVERAGE:

8-10 m<sup>2</sup>/Ltr/Coat (depending on surface condition)

### TECHNICAL DATA

<b>Color</b>	RED OXID GRAY
<b>Density @ 25 °c</b>	1.6 ±0.02 gm/cm <sup>3</sup>
<b>Thinner type &amp; Dilution %</b>	(white spirit) 10 % with Brush and Roller use 15 % with air spraying
<b>Finish</b>	Matt
<b>Flash Point</b>	40°C
<b>Initial drying time</b>	45 hours
<b>Recoat Time</b>	4-6 hours
<b>Final drying time</b>	24hours

### CLEAN UP INSTRUCTIONS:

- Clean up solvent: Clean, white spirit

### PACKAGING:

- 16kg Pails
- 3 kg gallon

### SHELF LIFE / STORAGE:

- Storage: must be stored in a cool, dry elevated place and protected from high humidity.
- Shelf Life: Up to 12 months in unopened containers, if stored as specified above.

### ENVIRONMENTAL & SAFETY

#### PRECAUTIONS:

- Do not store near food, drink or animal feed.
- Keep out of reach of children.
- Do not dispose of unwanted paint into drains, water sources or open sewers.
- For a full MSDS on this product, contact to MBC