

## JEFTINO ACRYLIC

### Interior & Exterior Acrylic Emulsion Paint

#### DESCRIPTION:

- **Jeftino acrylic** is a high quality emulsion paint have been developed and formulated to provide high hiding power ,lasting whiteness and great coverage for interior & exterior application.
- It provides a smooth sheen finish to interior & exterior walls.
- It have low VOC, hence maintaining a healthy home.

#### USES:

- **Jeftino acrylic** is used on interior & exterior walls, ceilings and hard & soft boards.

#### FEATURES AND BENEFITS:

- Smooth Sheen Finish.
- high hiding power and coverage
- Low VOC
- Cost of paint is low
- Good adhesion
- Provides uniform finish

#### SURFACE PREPARATION:

- **New surfaces :**
- New concrete must age at least 28 days, its pH must be less than 10 and it must be completely dry prior to priming

- Ensure that all dust, dirt and foreign matter are scraped and brushed away. Also ensure the surfaces are free from salts, oil, grease and ridges.
- **PRIMER:** Apply a coat of diluted Jeftino Sealer and allow drying for 6-8 hours.
- **PUTTY:** Smoothen the surface by filling dents with a thin coat of **Mastico**-wall putty /or Jeftino Cement putty and allow drying for 4-6 hours. Sand the surface with emery paper no.180 and wipe clean.
- **PRIMER:** Apply another coat of Jeftino sealer and allow drying for 6-8 hours..
- **Old surface:**
- Sand all glossy, rough, and patched surfaces. Feather back all rough edges to sound surface by sanding.
- **PUTTY:** repair the surface by filling dents cracks with a thin coat of Mastico wall putty and allow drying for 4-6 hours. Sand the surface with emery paper no.180 and wipe clean.
- **PRIMER:** Apply one coat of diluted Jeftino sealer and allow drying for 6-8 hours.

#### APPLICATION:

- **Stir thoroughly before using and occasionally when in use.**

- Dilute the paint with 20-30% water by volume.
- Apply two coats
- **JEFTINO ACRYLIC** is applied by using brush or roller.

#### coverage

- 1 kg cover 4-6 m<sup>2</sup> one coat

#### TECHNICAL DATA

Color	White
Density @ 25 °c	1.6 gm/cm <sup>3</sup>
PH @ 25 °c	9-9.5
Finish	Matt
Solvent	Potable water
Dry Time: To Touch	45 minutes
To Recoat	4-6 hours

#### CLEAN UP INSTRUCTIONS:

- Clean up solvent: Clean, potable water

#### PRECAUTIONS:

- Avoid painting when the temperature is below 10 degrees Celsius. Painting is not recommended if the moisture content and alkalinity of the walls is high. Moisture content of the walls should be below 16% and alkalinity of the wall should be below pH-10.
- Relative humidity should be below 85%. Painting on a newly plastered wall is recommended after 4 weeks of curing.

#### PACKAGING:

- 4.5 KG gallon
- 20 Kg Pails.
- 25 Kg Pails

#### SHELF LIFE / STORAGE:

- Storage: must be stored in a cool, dry elevated place and protected from high humidity.
- Shelf Life: Up to 12 months in unopened containers, if stored as specified above.

#### ENVIRONMENTAL & SAFETY

#### PRECAUTIONS:

- Do not store near food, drink or animal feed.
- Keep out of reach of children.
- Do not dispose of unwanted paint into drains, water sources or open sewers.
- For a full MSDS on this product, contact to MBC.