

WOOD ADHESIVE-MBC General Purpose Water Based PVA Adhesive

DESCRIPTION:

- **WOOD ADHESIVE-MBC** is a high performance PVA wood glue which when cured gives strong bonds in general carpentry, arts and crafts applications.
- **WOOD ADHESIVE-MBC** is a general purpose, indoor wood adhesive that is non-flammable and bonds in 24 hours.
- It gives a fast rate of bond strength development, good heat resistance and excellent adhesion on impact testing.

USES:

Applications include:

- General carpentry
- Arts & Crafts projects
- All woods, including softwood chipboard, blockwood, plywood and hardwood

FEATURES AND BENEFITS:

- Zero VOC water based
- Non Hazardous & Non flammable

Preparation and Application:

- **GENERAL USE**
 - Ensure that the surfaces to be bonded are smooth, clean and free from dust or other deposits.
 - Wood, plywood, laminated plastics etc. should be of uniform thickness. Some dense hardwoods may require sanding before bonding.
 - For best results the moisture content of the surfaces to be bonded should be within the range of 7 – 13% but when pressing at

temperatures above 105 C° moisture content should not exceed 10%.

• FLOORING USE

- For use with pre-finished, laminated and hardwood tongue and groove flooring.
- Apply the adhesive along the full length of the groove, on the top side of the board and also on the end joints.
- After each board has be positioned and tightly fixed using a hammering block, any excess adhesive should be removed with a damp cloth whilst still wet.

WOOD ADHESIVE-MBC may be applied by mechanical glue spreader or by hand using a brush or roller. Adhesive coverage between 80 and 180g sq/m are suitable depending on the surfaces to be bonded. When bonding different timbers such as teak and high-density hardwoods **WOOD ADHESIVE-MBC** should be applied to both surfaces of the joint. It should be noted that adhesive coverage has a considerable influence on both assembly and setting times (see below)

coverage

- **WOOD ADHESIVE-MBC** coverage between 80 and 180g sq/m are suitable depending on the surfaces to be bonded.
- When bonding different timbers such as teak and high-density hardwoods **WOOD ADHESIVE-MBC** should be applied to both surfaces of the joint. It should be noted that adhesive coverage has a considerable influence on both assembly and setting times

PACKAGING:

- **0.5 kg**
- **2.5 kg**



الشركة الحديثة لكيمويات البناء
Modern Building Chemicals

Product Technical Data

No.

Issue No.

Date

CLEAN UP INSTRUCTIONS:

- Wipe excess glue from joints with clean wet cloth before glue sets.
- Clean up excess and equipment with water prior to setting

PRECAUTIONS:

- Do not use on joints exposed to water or high humidity, not suitable for structural applications such as tables, chairs or other wooden furniture

SHELF LIFE / STORAGE:

- Shelf life is up to 12 months when stored in original, unopened container, Stored in a cool, dry place, out of direct sunlight.
- For maximum shelf life, store between 5° and 30°C.
- Do not allow product to freeze.
- Ensure containers are well sealed when not in use.

ENVIRONMENTAL & SAFETY

PRECAUTIONS:

- **WOOD ADHESIVE-MBC** is nonhazardous and nontoxic.
- Care should be taken when handling, that applicators wear PVC or similar gloves and safety goggles.
- For a full MSDS on this product, contact to MBC.