

900- ACRYLIC PAINT

A premium Quality Coating Based On Styrene Acrylic Polymer

DESCRIPTION:

- **Blato 900- Acrylic Paint** A premium quality acrylic emulsion paint with a smooth, finish durability and fungus resistance, for protection and decoration of all interior and exterior surfaces. It is ideal for application to all concrete, new or old masonry surfaces, gypsum boards, bricks, asbestos sheets etc.
- **Blato 900-Acrylic paint** has good flow , leveling , color retention properties and exhibits excellent washability .
- The product is available with eggshell, semi gloss and gloss finish.

USES:

Recommended for interior & exterior use on all new or old surfaces such as bricks, concrete surfaces, cement, gypsum boards and artificial stone.....etc.

FEATURES AND BENEFITS:

- Excellent Alkali Resistance
- Excellent Adhesion
- UV Resistance
- Anti-fungus & algae
- Good hiding power and coverage
- Low VOC
- Excellent weathering resistance
- Non yellowing
- Washable

SURFACE PREPARATION:

1. New surfaces :

- New concrete must age at least 28 days, its pH must be less than 10 and it must be completely dry prior to priming.
- Ensure that all dust, dirt and foreign matter are scraped and brushed away. Also ensure the

surfaces are free from salts, oil, grease and ridges.

- **PRIMER:** Apply a coat of diluted **Blato sealer** allow drying for 6-8 hours.
- **PUTTY:** Smoothen the surface by applying two coat of Blato wall putty /or **Blato Cement putty** and allow drying for 4-6 hours. Sand the surface with emery paper no.180 and wipe clean.
- **PRIMER:** Apply another coat of **Blato sealer** and allow drying for 6-8 hours. Before application of topcoat, sand the surface with emery paper no.320 and wipe clean.

2. Old surface :

- Sand all glossy, rough, and patched surfaces. Feather back all rough edges to sound surface by sanding.
- **PUTTY:** repair the surface by filling dents cracks with a thin coat of MASTICO wall putty and allow drying for 4-6 hours. Sand the surface with emery paper no.180 and wipe clean.
- **PRIMER:** Apply one coat of diluted **Blato sealer** and allow drying for 6-8 hours.

APPLICATION:

- Stir thoroughly before using and occasionally when in use.
- Dilute the paint with 10-20% water by volume.
- Apply two coats
- Allow 6 hours between each coat for complete drying.
- **Blato Acrylic** is applied by using brush or roller.

COVERAGE:

- 1L cover 10-12 m² one coat

TECHNICAL DATA

Color	White
PH @ 25 °c	9-9.5
Finish	Eggshell ,Semi gloss , Gloss
Solvent	Potable water
Dry Time: To Touch	45 minutes
To Recoat	4-6 hours

CLEAN UP INSTRUCTIONS:

- Clean up solvent: Clean, potable water

PRECAUTIONS:

- Avoid painting when the temperature is below 10 degrees Celsius. Painting is not recommended if the moisture content and alkalinity of the walls is high. Moisture content of the walls should be below 16% and alkalinity of the wall should be below pH-10.
- Relative humidity should be below 85%. Painting on a newly plastered wall is recommended after 4 weeks of curing.

PACKAGING:

- 4 USG Pails
- 3 LITTER

SHELF LIFE / STORAGE:

- Storage: must be stored in a cool, dry elevated place and protected from high humidity.
- Shelf Life: Up to 12 months in unopened containers, if stored as specified above.

ENVIRONMENTAL & SAFETY

PRECAUTIONS:

- Do not store near food, drink or animal feed.
- Keep out of reach of children.
- Do not dispose of unwanted paint into drains, water sources or open sewers.
- For a full MSDS on this product, contact to MBC